

## OIL223, OIL225



### TECHNICAL FEATURES:

- Head with side channel blower with three phase motor asynchronous, exposed to view
- Three phase centrifugal pump with rotor to discharge the liquid. power 0.55 kW and delivered quantity of 200 l/min with water
- Possibility to discharge the liquid at the same time it is sucked up (please refer to the procedures as mentioned in the "use and maintenance" instructions)
- Electric cable 10m. long with industrial plug 3Ph+T 16A
- Cartridge filter oil proof for oil mists Ø276x210mm
- Quick inlet Ø50mm
- Container for the collection of liquids of 220 l
- Container for the collection of shaving of 60l
- Rear wheels in cast iron Ø150mm, front wheels Ø150mm with brake
- Painted version in Ral 7001 (grey)
- Available also in single phase version
- Emptying hose Ø30 (4 m. long) with manual ball valve to discharge the sucked liquid
- Included in the supply accessories Ø50mm, K.AC.003:
  - 3mt oilproof flex hose Ø50 cod. 35.02.09.050
  - n.1 bent connection Ø50 cod. 65059
  - n.1 rubber cone oilproof Ø50 cod. 65053
  - n.1 oilproof conic nozzle Ø50 cod. 65072
  - n.1 hose connector Ø50 cod. 65044
  - n.2 hose clamp Ø50 cod. 30014

		OIL223	OIL225
Tension /Voltage	Volts	230-400V/50Hz	230-400V/50Hz
Power	Kw	3,55 (3+0.55)	6,05 (5.5+0.55)
Depression max	mbar max	320	320
Max working depression	mbar	260	260
Max air flow	m³/h	310	500
Liquids expulsion flow rate (with water)	Lt/m	200	200
Container capacity for chips	lt	60	60
Container capacity for liquids	lt	220	220
Product inlet	mm	Ø50	Ø50
Noise level	DbA	73	75
Overall dimensions	Cm	60x145x195h	60X145X210H
Weight	Kg	200	225
Protection	IP	55	55

**DustEx Solutions**, Shop No 42, Manav Vihar, Ambala City-134003, Haryana, India

Phone No.- +91 172-5198121 E-Mail- [sales@dustexsolutions.in](mailto:sales@dustexsolutions.in)

[www.dustexsolutions.in](http://www.dustexsolutions.in)