

A63MX1.3GD



TECHNICAL FEATURES:

- Machine body Ø460mm
- Side channel blower with single phase motor asynchronous marked ATEX EX II 3GD
- Electric cable 10mt long with industrial plug 2P+earth 16A IP67
- Manual filter shaker on side
- Star filter in polyester class "L" antistatic
- Quick inlet Ø70mm
- Container of 65 lt with handle and castors, in stainless steel
- Rear castors Ø150mm, front castors Ø125mm with brake, antistatic version

- Relief valve put in as standard
- standard version with trolley Ral 9005 black, container in stainless steel and filter chamber Ral 7001 grey
- X2 version with container and filter chamber in stainless steel
- We recommend the use of suction accessories Ø40mm e Ø50mm

		A63MX1.3GD
Tension /Voltage	Volts	1X230/50Hz
Power	Kw	2
Depression max	mbar max	300
Max working depression	mbar	200
Max air flow	m³/h	310
Primary filter surface	m²	1,90
Absolute filter surface	m²	2,20
Container capacity	Lt	65
Product inlet	mm	Ø70
Noise level	DbA	75
Overall dimensions	Cm	64x77x162h
Weight	Kg	78
Protection	IP	65
EX Marking	EX	II3G T4 II3D T135°C

DustEx Solutions, Shop No 42, Manav Vihar, Ambala City-134003, Haryana, India

Phone No.- +91 172-5198121 E-Mail- sales@dustexsolutions.in

www.dustexsolutions.in