

A21M, A22M



TECHNICAL FEATURES:

- Machine body Ø360mm
- Side channel blower with single phase motor asynchronous
- Vacuum-meter to control the filter efficiency
- Electric cable 9m with Schuko plug
- Manual filter shaker on side
- Star filter of polyester cat. "L" - Ø360mm, 8 pockets for A21M model
- Star filter of polyester cat. "L" - Ø360mm, 12 pockets for A22M model
- Quick inlet Ø70mm
- Waste bin of 25 l with integrated handle and castors
- Rear castors Ø125mm, front castors Ø100mm with brake
- Painted version with trolley Ral 9005 (black), container and filter chamber Ral 9003 (white)
- X1 version with waste bin in stainless steel
- X2 version with waste bin and filter chamber in stainless steel
- X3 version all in stainless steel
- We recommend using accessories of Ø40mm

| | | A21M | A22M |
|-------------------------|----------|---------------|---------------|
| Tension/ Voltage | Volts | 1Ph 230V/50Hz | 1Ph 230V/50Hz |
| Power | Kw | 1,1 | 1,5 |
| Depression max | mbar max | 250 | 250 |
| Max working depression | mbar | 200 | 200 |
| Max air flow | m³/h | 140 | 200 |
| Primary filter surface | m² | 0.70 | 1.14 |
| Absolute filter surface | m² | 1,20 | 1,20 |
| Container capacity | Lt | 25 | 25 |
| Product inlet | mm | Ø70 | Ø70 |
| Noise level | Dba | 65 | 67 |
| Overall dimensions | Cm | 47x61x118h | 47x61x135h |
| Weight | Kg | 55 | 60 |
| Protection | IP | 55 | 55 |

DustEx Solutions, Shop No 42, Manav Vihar, Ambala City-134003, Haryana, India

Phone No.- +91 172-5198121 E-Mail- sales@dustexsolutions.in

www.dustexsolutions.in