

## A63M



### TECHNICAL FEATURES:

- Machine body Ø460mm
- Side channel blower exposed to view with single phase motor asynchronous
- Electric cable 9m long with Schuko plug
- Manual filter shaker on side
- Star filter of polyester cat. "L" - Ø460mm
- Quick inlet Ø70mm
- 65l waste bin with integrated handle and castors
- Rear castors Ø150mm, front castors Ø125mm with brake
- Painted version with trolley Ral 9005 (black), container and filter chamber Ral 7001 (grey)
- X1 version with waste bin in stainless steel
- X2 version with waste bin and filter chamber in stainless steel
- Available with motor housing in painted version Ral7001 (grey) and in stainless steel
- We recommend using accessories of Ø40mm and Ø50mm

		A63M
Tension /Voltage	Volts	1X230/50Hz
Power	Kw	2.2
Depression max	mbar max	300
Max working depression	mbar	220
Max air flow	m³/h	310
Primary filter surface	m²	1,90
Absolute filter surface	m²	3.1
Container capacity	Lt	65
Product inlet	mm	Ø70
Noise level	DbA	75
Overall dimensions	Cm	64x77x162h
Weight	Kg	78
Protection	IP	55

**DustEx Solutions**, Shop No 42, Manav Vihar, Ambala City-134003, Haryana, India

Phone No.- +91 172-5198121 E-Mail- [sales@dustexsolutions.in](mailto:sales@dustexsolutions.in)

[www.dustexsolutions.in](http://www.dustexsolutions.in)