

## ONE63ECOC



### TECHNICAL FEATURES:

- Machine body Ø460mm
- 3 single phase brush motors double stage by-pass
- Head entirely made of metal black painted
- Independent switches for each motor
- Vacuum-meter and re light to control the filter efficiency
- Electric cable 9m with Schuko plug
- Kit cartridge filter Ø460 with 3 cartridges- total surface 5m<sup>2</sup>
- Automatic cleaning of the filters with compressed air jet
- Quick inlet Ø70mm
- Waste bin of 65 l with integrated handle and castors
- Rear castors Ø150mm, front castors Ø125mm with brake
- Painted version with trolley Ral 9005 (black), container and filter chamber Ral 7001 (grey)
- X1 version with waste bin in stainless steel
- Single phase compressor, power 1.5 and 24 l. tank

		ONE63ECOC
Tension /Voltage	Volts	1Ph 230V/50-60Hz
Power	Watt	5250 (3300+1500)
Depression max	mbar	210
Max air flow	m <sup>3</sup> /h	510
Primary filter surface	m <sup>2</sup>	5
Absolute filter surface	m <sup>2</sup>	NO
Container capacity	Lt	65
Product inlet	mm	Ø70
Noise level	DbA	-
Overall dimensions	Cm	
Weight	Kg	
Protection	IP	43

**DustEx Solutions**, Shop No 42, Manav Vihar, Ambala City-134003, Haryana, India

Phone No.- +91 172-5198121 E-Mail- [sales@dustexsolutions.in](mailto:sales@dustexsolutions.in)

[www.dustexsolutions.in](http://www.dustexsolutions.in)