

## ONE82WD , ONE82WP



### TECHNICAL FEATURES:

- Machine body Ø460mm
- 2 single phase brush motors double stage by-pass
- Head entirely made of metal black painted
- Independent switches for each motor
- Vacuum-meter and red light to control filter efficiency
- Electric cable 9m with Schuko plug
- Model WD: bag filter of polyester for dust, nylon filter, float for liquids and discharge hose Ø30x1.5m with cap
- Model WP: nylon filter, float for liquids, water pump and discharge hose Ø30x3m with manual valve
- Quick inlet Ø70mm
- Container with 80 l. capacity with handles and castors
- Rear castors Ø200mm, front castors Ø100mm with brake
- Model WD: painted version with trolley Ral 9005 (black) filter chamber Ral 7001 (grey) and X1 version with container in stainless steel
- Model WP: container in stainless steel and trolley black painted Ral 9005
- Supplied as standard along with the following accessories:
  - N.1 p/n 65042 Reduction 70/50 zinc coated
  - N.1 p/n 65164 Round brush Ø50
  - M.3 p/n 35134.1 polyurethane hose antistatic Ø50
  - N.2 p/n 65237A antistatic sleeve Ø50

		ONE82WD	ONE82WPX1
Tension/Voltage	Volts	1Ph 230V/50-60Hz	1Ph 230V/50-60Hz
Power	Watt	2200	2200
Depression max	mbar	210	210
Max air flow	m³/h	340	340
Primary filter surface	m²	0.58	-
Absolute filter surface	m²	-	-
Container capacity	Lt	85	85
Product inlet	mm	Ø70	Ø70
Noice level	Dba	76	76
Overall dimensions	Cm	55X60X126	55X60X126
Weight	Kg	30	30
Protection	IP	44	44

**DustEx Solutions**, Shop No 42, Manav Vihar, Ambala City-134003, Haryana, India

Phone No.- +91 172-5198121 E-Mail- [sales@dustexsolutions.in](mailto:sales@dustexsolutions.in)

[www.dustexsolutions.in](http://www.dustexsolutions.in)