

A1056KX1.3D



TECHNICAL FEATURES :

- Side channel blower with three phase motor asynchronous put in the back side of the vacuum cleaner into protective housing, marked EX II 3D
- Electric cable 10m long with industrial plug 3Ph+earth 32A IP 67 that can be disconnected from the vacuum cleaner
- Star filter Ø560 with big antistatic surface
- Manual filter shaker on top of the filter chamber
- Vacuum gauge to monitor the filter efficiency
- By-pass relief valve put in as standard
- Waste bin of 175l with castors and side handles for the emptying and as an option with lifting system for fork lift
- Quick inlet Ø100 for the quick inlet of accessories
- Fixed wheels Ø200 and revolving wheels Ø200 with brake on bearings to grant high manoeuvrability, antistatic
- standard version X1 with black trolley, machine Ral 7001 grey and container in stainless steel
- X2 version with container and filter chamber in stainless steel
- X3 version all in stainless steel
- Electric switchboard with soft-start to control the motor, already configured for remote control

		A1056KX1.3D
Tension/Voltage	Volts	400-690V/50Hz
Power	Kw	7,5
Depression max	mbar max	380
Max working depression	mbar	250
Max air flow	m³/h	820
Primary filter surface	m²	3,4 -Ø560
Upstream absolute filter	m²	NO
Downstream absolute filter	m²	18
Cartridge filter surface	m²	10
Container capacity	Lt	175
Product inlet	mm	Ø100
Noise level	DbA	78
Overall dimensions	Cm	74X157X178H
Weight	Kg	300
Protection	IP	55
EX Marking	EX	II3D T125°C

DustEx Solutions, Shop No 42, Manav Vihar, Ambala City-134003, Haryana, India

Phone No.- +91 172-5198121 E-Mail- sales@dustexsolutions.in

www.dustexsolutions.in