

A21X1.3D, A22X1.3D



TECHNICAL FEATURES:

- Machine body Ø360mm
- Side channel blower with three phase motor asynchronous marked ATEX EX II 3D
- Vacuum-meter to check filter efficiency
- Electric cable 10mt long with industrial plug 2P+earth 16A IP67 marked ATEX
- Manual filter shaker on side
- Star filter in polyester class "L" antistatic
- Quick inlet Ø70mm
- Relief valve put in as standard
- Container of 25 Lt with handle and castors, in stainless steel
- Rear castors Ø125mm, front castors Ø100mm with brake, antistatic version
- Standard version with trolley Ral 9005 black, container in stainless steel and filter chamber Ral 9003 white
- X2 version with container and filter chamber in stainless steel
- X3 version completely in stainless steel
- We recommend the use of suction accessories Ø40mm

		A21X1.3D	A22X1.3D
Tension /Voltage	Volts	230-400V/50Hz	230-400V/50Hz
Power	Kw	1.1	1.5
Depression max	mbar	200	200
Max air flow	m³/h	140	200
Primary filtering surface	m²	0,70	1,14
Absolute filtering surface	m²	1,20	1,20
Container capacity	Lt	25	25
Product inlet	mm	Ø70	Ø70
Noise level	dB(A)	65	67
Overall dimensions	Cm	47x61x118h	47x61x118h
Weight	Kg	55	60
Protection	IP	55	65
EX Marking	EX	II3D T125°C	II3D T135°C

DustEx Solutions, Shop No 42, Manav Vihar, Ambala City-134003, Haryana, India

Phone No.- +91 172-5198121 E-Mail- sales@dustexsolutions.in

www.dustexsolutions.in