

A63X1.3GD, A65X1.3GD



TECHNICAL FEATURES:

- Machine body Ø460mm
- Side channel blower with single phase motor asynchronous marked ATEX EX II 3GD
- Electric cable 10m long with industrial plug 3 Ph+earth 16A IP67
- Manual filter shaker on side
- Star filter of polyester cat. "L" antistatic
- Quick inlet Ø70mm
- Container of 65 Lt with handle and castors, in stainless steel
- Relief valve put in as standard
- Rear wheels Ø150mm, front wheels Ø125mm with brake, antistatic
- standard version with trolley Ral 9005 black, container in stainless steel and filter chamber Ral 7001 grey
- X2 version with container and filter chamber in stainless steel
- We recommend the use of suction accessories Ø40mm e Ø50mm

		A63X1.3GD	A65X1.3GD
Tension / Voltage	Volts	230-400V/50Hz	230-400V/50Hz
Power	Kw	2.6	5.2
Depression max	mbar max	300	290
Max working depression	mbar	220	220
Max air flow	m³/h	320	520
Primary filter surface	m²	1,90	1,90
Absolute filter surface	m²	2,20	2,20
Container capacity	Lt	65	65
Product inlet	mm	Ø70	Ø70
Noise level	DbA	75	77
Overall dimensions	Cm	64x77x162h	64x77x162h
Weight	Kg	77	93
Protection	IP	65	65
Ex Marking	EX	II 3G T4 II3D T135°C	II 3G T4 II3D T135°C

DustEx Solutions, Shop No 42, Manav Vihar, Ambala City-134003, Haryana, India

Phone No.- +91 172-5198121 E-Mail- sales@dustexsolutions.in

www.dustexsolutions.in