

BA2205, BA2805, BA281



TECHNICAL FEATURES:

- Side channel blower with asynchronous motor, three phase or single phase, exposed to view
- C version, with motor into protective housing white painted
- Filter body Ø220 for model BA2205
- Filter body Ø280 for models BA2805, BA281
- Bag filter of polyester cat. "L", without manual filter shaker
- Straight inlet Ø40mm
- Base of support
- Standard version in painted steel RAL 9003 (white)
- X version: all in stainless steel (both filter chamber and base of support), motor exposed to view
- T version: with magneto-thermal switch into IP 55 box
- CX2 version: all in stainless steel

		BA2205	BA2805	BA281
Tension /Voltage	Volts	230-400V/50Hz	230-400V/50Hz	230-400V/50Hz
Power	kW	0.37	0.37	0.90
Depression max	mbar	160	160	230
Max working depression	mbar	110	110	150
Max air flow	m³/h	80	80	150
Primary filtering surface	m²	0.15	0.23	0.23
Absolute filtering surface	m²	NO	1,20	1,20
Container capacity	Lt	3	9	9
Product inlet	mm	Ø40	Ø40	Ø40
Noise level	DbA	70	70	70
Overall dimensions	Cm	35X60X46H	35X60X46H	35X60X45H
Weightl	Kg	20	22	30
Protection	IP	54	54	54

DustEx Solutions, Shop No 42, Manav Vihar, Ambala City-134003, Haryana, India

Phone No.- +91 172-5198121 E-Mail- sales@dustexsolutions.in

www.dustexsolutions.in

BA3605, BA361, BA362, BA363, BA465



TECHNICAL FEATURES:

- Side channel blower with asynchronous motor, three phase or single phase, exposed to view
- C version with motor into protective housing white painted
- Filter body Ø360
- Star filter of polyester cat. "L"
- Manual filter shaker
- Straight inlet Ø50mm
- Base of support
- Standard version in painted steel RAL 9003 (white)
- X version all in stainless steel (both filter chamber and support) and motor exposed to view
- T version : with magneto-thermal switch into IP 55 box

		BA3605	BA361	BA362	BA363	BA465
Tension /Voltage	Volts	230-400V/50Hz	230-400V/50Hz	230-400V/50Hz	230-400V/50Hz	230-400V/50Hz
Power	kW	0.37	0.90	1.5	2.2	4
Depression max	mbar	160	230	250	310	400
Max working depression	mbar	110	150	210	200	200
Max air flow	m³/h	80	150	210	310	520
Primary filtering surface	m²	0.70	0.70	0.70	0.70	1.9
Absolute filtering surface	m²	3.1	3.1	3.1	3.1	3.1
Container capacity	Lt	12	12	12	12	25
Product inlet	mm	Ø50	Ø50	Ø50	Ø50	Ø70
Noise level	DbA	70	70	64	73	78
Overall dimensions	Cm	39X80X64H	39X80X64H	39X80X64H	39X80X64H	46X105X85H
Weightl	Kg	30	35	42	52	62
Protection	IP	54	54	55	54	54

DustEx Solutions, Shop No 42, Manav Vihar, Ambala City-134003, Haryana, India

Phone No.- +91 172-5198121 E-Mail- sales@dustexsolutions.in

www.dustexsolutions.in