

AS1556, AS256, AS356



TECHNICAL FEATURES:

- Side channel blower with asynchronous motor, three phase or single phase as option, located at the bottom under the container
- Machine body Ø560mm
- Electric cable 10m long with industrial plug 3Ph+ Earth 16A
- Bylon filter bag 200 micron
- Inspection window on the cover to check the filter bag
- Straight inlet Ø70
- Container of 150 l.
- Wheels Ø63mm with brake
- Standard version painted RAL 9003 (white)
- X version with container and cover in stainless steel

		AS1556	AS256	AS356
Tension/ Voltage	Volts	230-400V/50Hz	230-400V/50Hz	230-400V/50Hz
Power	kW	1.1	1.5	2.2
Depression max	mbar max	230	250	310
Max working depression	mbar	175	210	200
Max air flow	m ³ /h	150	210	310
Primary filter surface	m ²	NO	NO	NO
Upstream absolute filter	m ²	NO	NO	NO
Downstream absolute filter	m ²	1,3	1,3	1,3
Cartridge filter surface	m ²	NO	NO	NO
Container capacity	Lt	150	150	150
Product inlet	mm	Ø70	Ø70	Ø70
Noise level	DbA	70	64	73
Overall dimensions	Cm	Ø56X116H	Ø56X116H	Ø56X116H
Weight	Kg	60	65	72
Protection	IP	54	55	54

DustEx Solutions, Shop No 42, Manav Vihar, Ambala City-134003, Haryana, India

Phone No.- +91 172-5198121 E-Mail- sales@dustexsolutions.in

www.dustexsolutions.in