

AS1556X.3D, AS356X.3D



TECHNICAL FEATURES:

- Side channel blower with asynchronous motor, three phase or single phase as option, located at the bottom under the container. Marked ATEX EX II 3D
- Machine body Ø560mm
- Electric cable 10m long with industrial plug 3Ph+ earth 16A IP67
- Nylon filter bag antistatic to collect the product
- Inspection window on the cover to check the filter bag
- Relief valve put in as standard
- Straight inlet Ø70

- Container of 150 l in stainless steel
- Wheels Ø63mm with brake, antistatic version

		AS1556X.3D	AS356X.3D
Tension/ Voltage	Volts	230-400V/50Hz	230-400V/50Hz
Power	Kw	1.5	2.6
Depression max	mbar max	250	300
Max working depression	mbar	200	220
Max air flow	m³/h	210	310
Primary filter surface	m²	NO	NO
Upstream absolute filter	m²	NO	NO
Downstream absolute filter	m²	1,3	1,3
Cartridge filter surface	m²	NO	NO
Container capacity	Lt	150	150
Product inlet	mm	Ø70	Ø70
Noise level	DbA	70	73
Overall dimensions	Cm	Ø56X116H	Ø56X116H
Weight	Kg	60	72
Protection	IP	55	55
EX Marking	EX	II3D T125°C	II3D T125°C

DustEx Solutions, Shop No 42, Manav Vihar, Ambala City-134003, Haryana, India

Phone No.- +91 172-5198121 E-Mail- sales@dustexsolutions.in

www.dustexsolutions.in