

A1056 , A1056K



TECHNICAL FEATURES :

- Side channel blower with three phase motor asynchronous put in the back side of the vacuum cleaner into protective housing
- Electric cable 10m long with industrial plug 3Ph+T 32A that can be disconnected from the vacuum cleaner
- Star filter Ø560 with big surface
- Manual filter shaker on top of the filter chamber
- Vacuum gauge to monitor the filter efficiency
- By-pass relief valve put in as standard
- Waste bin of 175l with castors and side handles for the emptying and as an option with lifting system for fork lift
- Quick inlet Ø100
- Fixed wheels Ø200 and revolving wheels Ø200 with brake on bearings to grant high manoeuvrability
- Painted version with frame RAL 9005 (black) and machine Ral 7001 (grey)
- X1 version with waste bin in stainless steel
- X2 version with container and filter chamber in stainless steel
- X3 version all in stainless steel
- Electric switchboard with soft-start and PLC to control the motor, already configured for remote control

| | | A1056 | A1056K |
|----------------------------|----------|---------------|---------------|
| Tension/Voltage | Volts | 400-690V/50HZ | 400-690V/50Hz |
| Power | Kw | 7,5 | 7,5 |
| Depression max | mbar max | 520 | 380 |
| Max working depression | mbar | 400 | 250 |
| Max air flow | m³/h | 540 | 820 |
| Primary filter surface | m² | 3,4 -Ø560 | 3,4 -Ø560 |
| Upstream absolute filter | m² | NO | NO |
| Downstream absolute filter | m² | 7,25 | 18 |
| Cartridge filter surface | m² | 10 | 10 |
| Container capacity | Lt | 175 | 175 |
| Product inlet | mm | Ø100 | Ø100 |
| Noise level | DbA | 74 | 78 |
| Overall dimensions | Cm | 74X157X187H | 74X157X187H |
| Weight | Kg | 375 | 300 |
| Protection | IP | 55 | 55 |

DustEx Solutions, Shop No 42, Manav Vihar, Ambala City-134003, Haryana, India

Phone No.- +91 172-5198121 E-Mail- sales@dustexsolutions.in

www.dustexsolutions.in