

A136, A236



TECHNICAL FEATURES:

- Side channel blower with three phase asynchronous motor or single phase as option, placed into a protective housing
- Electric cable 10m long with industrial plug 3Ph+T 16A
- Vacuum meter to control filter efficiency
- Machine body Ø360mm
- Manual filter shaker on top
- Star filter of polyester cat. "L"
- Quick inlet Ø70mm
- Waste bin of 25 l with handles, removable
- Rear castors Ø125mm, front castor Ø100mm with

brake

- Painted version with frame, container and filter chamber in Ral 9003 (white)
- X1 version with waste bin in stainless steel
- X2 version with waste bin and filter chamber in stainless steel
- X3 version all of stainless steel

		A136	A236
Tension/ Voltage	Volts	230-400V/50Hz	230-400V/50Hz
Power	Kw	0,9	1,5
Depression max	mbar max	230	250
Max working depression	mbar	150	210
Max air flow	m³/h	150	210
Primary filter surface	m²	0,70	0,70
Upstream absolute filter	m²	NO	NO
Downstream absolute filter	m²	4,8	4,8
Cartridge filter surface	m²	NO	NO
Container capacity	Lt	25	25
Product inlet	mm	Ø70	Ø70
Noise level	Dba	70	64
Overall dimensions	Cm	40X70X126h	40X70X126h
Weight	Kg	69	71
Protection	IP	55	55

DustEx Solutions, Shop No 42, Manav Vihar, Ambala City-134003, Haryana, India

Phone No.- +91 172-5198121 E-Mail- sales@dustexsolutions.in

www.dustexsolutions.in