

A346EP - A546KEP



TECHNICAL FEATURES:

- Side channel blower with three phase motor asychronous placed in the back side into a protective housing with ABS cover
- Electric cable 10m long with industrial plug 3Ph+T 16A
- Star filter Ø460 cat. "L" with big filtering surface
- manual filter shaker on top of the filter chamber
- · Vacuum-meter to control the filter efficiency
- Waste bins of 39, 65 and 100 l.
- •In the 39I and 65I versions, the waste bin has got the integrated handle and it is equipped with castors
- In the 100 I. models, the wastre bin is on castors and equip-

ped with two handles; as an option it can be fitted with a clamp to take it up with a fork lift

- Quick inlet Ø70
- Accessories compartment and support for the flex. hose in the front side
- Support cable reeler in the back side
- Painted version in Ral 7001 grey
- X1 version with waste bin in stainless steel
- Fixed wheels Ø150mm and revolving wheels with brake Ø125mm
- Relief valve put in as standard only for A546KEP
- For version with protection degree IP65, refer to the ATEX version

		A346/30EP	A346EP	A546/30KEP	A546KEP
		A346/60EP		A546/60KEP	
Tension /Voltage	Volts	230-400V/50Hz	230-400V/50Hz	230-400V/HZ	230-400V/50Hz
Power	Kw	2,2	2,2	4	4
Depression Max	mbar max	300	300	290	290
Working depression	mbar	200	200	200	200
Max air flow	m³/h	310	310	520	520
Primary filter surface	m²	1,90	1,90	1,90	1,90
Upstream absolute filter surface	m²	3.1	3.1	3.1	3.1
Downstream absolute filter surface	m²	NO	NO	NO	NO
Cartridge filter surface	m²	5	5	5	5
Container capacity	Lt	39 / 65	100	39 / 65	100
Product inlet	mm	Ø70	Ø70	Ø70	Ø70
Noise level	Dba	74	74	76	76
Overall dimensions	Cm	64X113X123H (30LT) 64X113X134H (60LT)	64X113X160H	64X113X123H (30LT) 64X113X134H (60LT)	64X113X160H
Weight	Kg	115 (30LT) / 120 (60LT)	130	142 (3017) / 160 (6017)	170
Protection	IP	55	55	55	55