

F230



TECHNICAL FEATURES:

- Side channel blower with asynchronous motor three phase or in option single phase, placed into a protective housing
- Electric cable 10m long with industrial plug 3Ph+ T 16A
- Vacuum meter to control the filter efficiency
- Body of the machine Ø360mm
- Manual filter shaker on top
- Star filter of polyester cat. "L"
- Quick inlet Ø70mm
- Waste bin of 25 l with handles, removable
- Rear castors Ø125mm, front castors Ø100mm with

brake

- Painted version with fram, waste bin and filter cahmber Ral 9003 (white)
- X1 version with container in stainless steel
- X2 versione with container and filter chamber in stainless steel
- X3 version with waste bin, filter chamber and frame in stainless steel
- Quick installation of alll options

| | | F230 |
|----------------------------|----------|---------------|
| Tension /Voltage | Volts | 230-400V/50Hz |
| Power | Kw | 1,5 |
| Depression Max | mbar max | 250 |
| Working Depression | mbar | 210 |
| Max air flow | m³/h | 210 |
| Primary filter surface | m² | 0,70 |
| Upstream absolute filter | m² | 1.55 |
| Downstream absolute filter | m² | 4,8 |
| Cartridge filer surface | m² | NO |
| Container capacity | Lt | 25 |
| Product inlet | mm | Ø70 |
| Noise level | DbA | 64 |
| Overall dimensions | Cm | 40X70X151h |
| Weight | Kg | 90 |
| Protection | IP | 55 |

DustEx Solutions, Shop No 42, Manav Vihar, Ambala City-134003, Haryana, India

Phone No.- +91 172-5198121 E-Mail- sales@dustexsolutions.in

www.dustexsolutions.in