

F340



TECHNICAL FEATURES:

- Side channel blower with three phase asynchronous motor, placed into protective housing
- Electric cable 10m long with industrial plug 3Ph+ Earth 16A
- Vacuum-meter to monitor the filter efficiency
- Machine body Ø460mm
- Manual filter shaker on top
- Star filter of polyester cat. "L"
- Quick inlet Ø70mm
- Dust bin of 48 l. with handles, removable
- Rear castors Ø125mm, front castors Ø100mm with brake
- Painted version with frame, dust bin and filter chamber in painted steel RAL 9003 (white)
- X1 version with dust bin in stainless steel
- X2 version with dust bin and filter chamber in stainless steel
- X3 version with dust bin, filter chamber and frame in stainless steel
- Easy installation of options and accessories

		F340
Tension / Voltage	Volts	230-400V/50Hz
Power	Kw	2.2
Max depression	mbar max	310
Max working depression	mbar	200
Max air Flow	m ³ /h	310
Primary filter surface	m ²	1,90
Upstream absolute filter	m ²	2,2
Downstream absolute filter	m ²	4,8
Cartridge filter kit	m ²	5
Container capacity	Lt	48
Product inlet	mm	Ø70
Noise level	DbA	73
Overall dimensions	Cm	50X80X154h
Weight	Kg	120
Protection	IP	55

DustEx Solutions, Shop No 42, Manav Vihar, Ambala City-134003, Haryana, India

Phone No.- +91 172-5198121 E-Mail- sales@dustexsolutions.in

www.dustexsolutions.in